



EFG014025

## Izi Pro

Izi Pro is a series of metal sit/stand workstation frames with T-feet and rectangular legs. The leg has the thickest part turned upward. The table has motorized height adjustment.

## Product info

- With Izi Pro workstations you have the possibility to combine table tops and frames within the limits that design and standard allows.
- Izi Pro has a large number of table tops.
- Table tops with straight edges: 22 mm core of chip board with 0.6 mm veneer in beech (R5), ash white 2% (A2) and Birch (B5). Table tops in MFC (MB, MC, ML, MV, M6 and MA), HPL (HW) or linoleum (D4) have a 22 mm core of chip board and straight edges.
- The frame is available with both two or three legs.
- Motor-driven height adjustment with two motors, stroke: 650 mm height 640-1290 mm.
- Anti-collision (frame stops automatically when colliding with an obstacle)
- Available with sliding table top as additional for an easy cable access and to create a clean surface. Please note that the smallest table top size is 1400 mm when choosing sliding table top.
- Metal frame with rectangular legs with the placement of the thickest part upwards and T-foot. Black structure (24), silver (62), or white (Z4).
- The frame has adjustable beams between the lengths 1000 and 1800 mm, which is suitable for table tops from 1200 to 2000 mm.
- Maximum load: 125 kg (excluding table top; an EFG top 800x1800 mm weighs 20 kg)
- Assembling: Frame is fixed directly to the table top with enclosed screws.
- Accessories: Desk screens, modesty panels, cable management, CPU-holder and wall mount for flat screens.
- Guarantee: Five years liability for defects resulting from faulty design, materials or workmanship.
- Material meets approved industry standards and environmental requirements.
- Certified by "Möbelfakta" for quality, environmental and Social responsibility.
- Tested according to EN 527-1:2011, EN 527-2:2016, EN 1730:2012 and ISO 21016:2007, Type A Fully adjustable.

## TECHNICAL INFO:

- Power supply: 240 V.
- Speed, 45 kg: 32 mm/s.
- Stroke 500 och 650 mm.
- Maximum load: 125 kg (excluding table top; an EFG top 800x1800 mm weighs 20 kg)
- Overheating protection: 1 min operation, 9 min rest.
- Sound 45 dB
- Consumption in standby: 0,10 W (two legs) 0,20 W (Three legs)
- Temperature in the surroundings during operation: +5 till +40° C

EFG014028



EFG014036



EFG014030



EFG014031



EFG014033



Izi Pro, height control